

UNITED STATES PATENT AND TRADEMARK OFFICE CERTIFICATE OF CORRECTION

Page 1 of 2

PATENT NO. : 7,423,337
APPLICATION NO. : 10/707,208
ISSUE DATE : Sep. 9, 2008
INVENTOR(S) : Patwardhan et al.

It is certified that an error appears or errors appear in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

In the Face of the Patent:

(75) **Inventors:** Change "Nikhil K. Kelhar" to --Nikhil V. Kelhar--.

In the Specification:

Column 6, after line 39, insert --Referring to FIG. 5C, the semiconductor die of FIG. 5B is shown as being permanently attached to a substrate, such as PCB 120, in accordance with one embodiment of the present invention. As illustrated, a single die 100 has been aligned with contacts on a PCB 120 and permanently attached through the reflowing of the solder bumps of the die and the solder paste of the PCB to form multiple solder joint connections 130. Because of the presence of the sufficiently rigid support coating 160, however, the shape of each solder joint 130 is substantially constrained in comparison with a typical solder joint 30, as seen in FIGS. 2C and 3. As indicated above, the support coating 160 has provided structural support to the solder bumps 112 during the reflow process, such that the extent of the collapse of the solder joints has been constrained. In addition, the support coating 160 is also able to provide structural support to the subsequent solder joint connections 130.--.

MAILING ADDRESS OF SENDER (Please do not use customer number below):

Justin A. White
BEYER LAW GROUP LLP
P.O. Box 1687
Cupertino, CA 95015-1687

This collection of information is required by 37 CFR 1.322, 1.323, and 1.324. The information is required to obtain or retain a benefit by the public which is to file (and by the USPTO to process) an application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.14. This collection is estimated to take 1.0 hour to complete, including gathering, preparing, and submitting the completed application form to the USPTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions for reducing this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, P.O. Box 1450, Alexandria, VA 22313-1450. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Attention Certificate of Corrections Branch, Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.

UNITED STATES PATENT AND TRADEMARK OFFICE CERTIFICATE OF CORRECTION

Page 2 of 2

PATENT NO. :

APPLICATION NO. :

ISSUE DATE :

INVENTOR(S) :

It is certified that an error appears or errors appear in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

Col. 6, line 46, delete "tie".

Col. 6, beginning at line 62 and ending with Col. 7, line 14, delete "Continuing on to FIG. 6, a particular solder joint between the PCB and semiconductor die with a sufficiently rigid support coating of FIG. 5C is similarly illustrated in side cross-sectional view. Compared to the conventional solder joint 30 of FIG. 3, the solder joint 130 of FIG. 6 is superior in several ways. One significant improvement can be found in the wetting angle 131 between the solder joint 130 and the die 100. If the height of the support coating is at about fifty percent of the original solder bump height, the final wetting angle 131 is typically between 50 and 60 degrees, which is markedly better than the normally resulting angle of about 25 to 35 degrees. In some instances, the final wetting angle 131 is almost equal to the pre-collapse angle between the original solder bump 112 and die 100. In any event, this significant increase in the final wetting angle substantially increases the structural strength of the formed solder joints, which improves solder joint reliability and lifespan under temperature cycling. In fact, preliminary experimental results indicate that reliability and lifespan are at least doubled for solder joints in dice having a sufficiently rigid support coating."

MAILING ADDRESS OF SENDER (Please do not use customer number below):

Justin A. White
BEYER LAW GROUP LLP
P.O. Box 1687
Cupertino, CA 95015-1687

This collection of information is required by 37 CFR 1.322, 1.323, and 1.324. The information is required to obtain or retain a benefit by the public which is to file (and by the USPTO to process) an application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.14. This collection is estimated to take 1.0 hour to complete, including gathering, preparing, and submitting the completed application form to the USPTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions for reducing this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, P.O. Box 1450, Alexandria, VA 22313-1450. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Attention Certificate of Corrections Branch, Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.